Organization IC 2600

THE PERSON

AN EQUAL OPPORTUNITY EMPLOYER

USPTO MAIL CENTER OCT 2 5 2005

ALEXANDRIA, VA 22313-1450 IF UNDELIVERABLE RETURN IN TEN DAYS U. S. DEPARTMENT OF COMMERCE COMMISSIONER FOR PATENTS P.O. BOX 1450

OFFICIAL BUSINESS

BUCH695 FORWARD TIME EXP S024 1604 17 10/ FUDOLDH J BUCHEL RTN TO SEND DALLAS TX 75370-2526

indialahalihan to sender Mahalahalahaliahaliahalaha

THW



# United States Patent and Trademark Office

UNITE J. TATES I PARTITUDIT OF COMMERCE United States Pate... and T. ... Aug.: Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/612,125	07/02/2003	Andrew Weeks Kueny	946959-600013	3892
75	90 10/05/2005		EXAM	INER
RULDOLPH J	I. BUCHEL		MISLEH, J	IUSTIN P
P.O. BOX 7936 DALLAS, TX	= =		ART UNIT	PAPER NUMBER
			2612	
			D. TT. 14. 11 TD. 10/05/2004	_

DATE MAILED: 10/05/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

RECEIVED OIPE/IAP

OCT 2 6 2005

	Application No.	Applicant(s)
	10/612,125	KUENY, ANDREW WEEKS
Office Action Summary	Examiner	Art Unit
	Justin P. Misleh	2612
The MAILING DATE of this communication app	ears on the cover sheet with the c	correspondence address
Period for Reply	VIO OET TO EVOIDE AMONTU	(C) FDOM
A SHORTENED STATUTORY PERIOD FOR REPL' THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a repl' - If NO period for reply is specified above, the maximum statutory period.  - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be tin y within the statutory minimum of thirty (30) day will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	nely filed s will be considered timely. I the mailing date of this communication. D (35 U.S.C. § 133).
Status		
1) Responsive to communication(s) filed on	 	
/ <u> </u>	action is non-final.	
3) Since this application is in condition for allowa		
closed in accordance with the practice under E	Ex parte Quayle, 1935 O.D. 11, 4	53 O.G. 213.
Disposition of Claims		
4) $\boxtimes$ Claim(s) <u>1 - 50</u> is/are pending in the application	n.	
4a) Of the above claim(s) is/are withdra		
5) Claim(s) is/are allowed.		
6)⊠ Claim(s) <u>1 – 4, 14 – 16, 23 – 29, and 33 – 50</u> i		
7)⊠ Claim(s) <u>5 – 13, 17 – 22, and 30 – 32</u> is/are ol	ojected to.	
8) Claim(s) are subject to restriction and/o	or election requirement.	
Application Papers		
9)⊠ The specification is objected to by the Examine	er.	
10) $\boxtimes$ The drawing(s) filed on <u>02 July 2003</u> is/are: a)		
Applicant may not request that any objection to the		
Replacement drawing sheet(s) including the correct		
11)☐ The oath or declaration is objected to by the E	Kamimer, Note the attached Office	ACTOL OF TOWN 1 10-132.
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document	•	)-(d) or (f).
2. Certified copies of the priority document		ion No
3. ☐ Copies of the certified copies of the prior		
application from the International Burea		
* See the attached detailed Office action for a list	of the certified copies not receive	ed.
,		
Attachment(s)  1) ⊠ Notice of References Cited (PTO-892)	4) Interview Summary	/ (PTO-413)
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Mail D	ate Patent Application (PTO-152)
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 7/2/03.	6) Other:	etent Application (F 10-102)
	<u> </u>	

Art Unit: 2612

### **DETAILED ACTION**

# Specification

1. The disclosure is objected to because it contains an embedded hyperlink and/or other form of browser-executable code (see pages 3 and 4). Applicant is required to delete the embedded hyperlink and/or other form of browser-executable code. See MPEP § 608.01.

## Claim Objections

- 2. Claim 28 is objected to because of the following informalities: lack of clarity and precision.
- 3. Claim 28, the claim language relies on several items as being previously introduced (e.g. "the N linear pixel arrays" and "the N registers"), but no previous introduction has given for those respective items. Appropriate correction is required.

# Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 5. Claims 1-4, 14-16, 23-29, and 33-50 are rejected under 35 U.S.C. 102(b) as being anticipated by West.

Art Unit: 2612

6. For Claim 1, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 – 67), column 5 (lines 1 – 3, 10 – 27, and 56 – 62), and column 6 (lines 11 – 13), a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

integrating charge in at least some pixels of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 – 59);

combining charge from a first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and column 5, lines 1 – 3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

Art Unit: 2612

representing charge from at least a portion of the first region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.);

combining charge from a second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); and

representing charge from at least a portion of the second region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.).

Art Unit: 2612

The CCD spectroscopy of West, as stated in column 3 (lines 10 - 18 and 30 - 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- As for Claim 2, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N first region data signals; and presenting said portion of N second region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).
- 8. As for Claim 3, West discloses wherein said first portion comprises N first region data signals (4 or 8 rows) and said second portion comprises N second region data signals (also 4 or 8 rows).

West states, since both the light and dark alternating area are eight rows high, the resulting arrangement is two rows of a spectrum comprising four binned rows of spectra and tow rows comprising dark charge.

- As for Claim 4, West discloses, as stated in columns 4 (lines 47 67) and 5 (lines 1 4), defining the first region of the N linear pixel arrays of the imaging sensor (300) by designating at least one pixel line (4 or 8 lines) as belonging to the first region (401) of the N linear pixel arrays.
- 10. As for Claim 14, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the

Art Unit: 2612

device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 – column 5, line 4). Hence, West discloses wherein defining the first region (401) of the N linear pixel arrays of the imaging sensor is accomplished during a setup phase of a device incorporating said imaging sensor.

- 11. As for Claim 15, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 column 5, line 4).

  Furthermore, West discloses, in column 4 (line 47) column 5 (line 4) and in column 5, lines 27 40), a four to one binning ratio can be used to compress 320 rows in region 301 into 80 rows in region 302 by an arrangement which bins according to the following algorithm: 5 to 1, 5 to 1, 4 to 1, 4 to 1, 2 to 1, 5 to 1, 5 to 1, 4 to 1, 2 to 1, repeat, etc. Hence, West discloses wherein defining the first region of the N linear pixel arrays of the imaging sensor is accomplished dynamically, following said integrating charge in at least some pixels of the N linear pixel arrays, and prior to a subsequent integration of charge in at least some pixels of the N linear pixel arrays.
- 12. As for Claim 16, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 column 5, line 4).

  Furthermore, West discloses, in column 4 (line 47) column 5 (line 4) and in column 5, lines 27 40), a four to one binning ratio can be used to compress 320 rows in region 301 into 80 rows in

Art Unit: 2612

region 302 by an arrangement which bins according to the following algorithm: 5 to 1, 5 to 1, 4 to 1, 4 to 1, 2 to 1, 5 to 1, 5 to 1, 4 to 1, 2 to 1, repeat, etc. Hence, West discloses wherein defining the first region of the N linear pixel arrays of the imaging sensor is accomplished dynamically, following said integrating charge in at least some pixels of the N linear pixel arrays, and prior to a subsequent integration of charge in at least some pixels of the N linear pixel arrays. Hence, the Examiner considers any region with four rows to be binned as small-amplitude signals and any region with eight rows to be binned as large-amplitude signals.

- 13. As for Claim 23, the CCD spectroscopy of West, as stated in column 3 (lines 10 18 and 30 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region. Therefore, while not specifically shown or states, it must be that wherein a corresponding each of said portion of N first region data signals and each of said portion of N second region data signals both correspond to at least one discrete wavelength.
- As for Claim 24, West discloses, as shown in figures 4 and 5 and as stated in column 4 (line 47) column 5 (line 3) and column 5 (lines 27 40), combining (in CCD region 302; see figure 5) a part of said portion of N first region data signals (401) with a non-corresponding part of said portion of N second region data signals (402); and presenting the part of said portion of N first region data signals and the non-corresponding part of said portion of N second region data signals as a plurality of data signals.

West discloses multiline spectroscopy is provided with a plurality of different spectra.

West also discloses kinetic spectroscopy is provided with a single spectrum.

Art Unit: 2612

For Claim 25, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29-67), column 5 (lines 1-3, 10-27, and 56-62), and column 6 (lines 11-13), an imaging apparatus (300) comprising an imaging sensor (300) comprising:

N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M charge coupled pixels (1340 M Rows);

M pixel lines (1340), said M pixel lines being oriented in generally orthogonal direction to the N linear pixel arrays;

N registers (304), wherein one pixel in each of the N linear pixel arrays being charge coupled to a respective one of the N registers;

signal converter (amplifier in figures 4 and 5 that corresponds to amplifier 104 in figure 1);

an output node coupled to said signal converter (see output line extending from said signal converter);

a memory connected to said output node (although not specifically shown; a must have feature of the CCD image sensor 300);

a readout controller coupled to said imaging sensor for controlling readout of said M charge coupled pixels in all the N linear pixel arrays (although not specifically shown; a must have feature of the CCD image sensor 300); and

means for instructing said readout controller (see column 6, lines 11 - 13) for combining charge from a first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting

Art Unit: 2612

charge from the first region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67). said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays; shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); combining charge from a second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays; shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67).

The CCD spectroscopy of West, as stated in column 3 (lines 10 - 18 and 30 - 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

16. As for Claim 26, West discloses wherein said memory being coupled to a display device (although not specifically shown; a must have feature of the spectroscopy system of West)

Art Unit: 2612

17. As for Claim 27, West discloses two modes for spectroscopy including kinetic and multiline. West discloses, as stated in column 5 (line 64) – column 6 (line 13), programming the device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout controller (also see column 4, line 47 – column 5, line 4).

18. For Claim 28, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 – 67), column 5 (lines 1 – 3, 10 – 27, and 56 – 62), and column 6 (lines 11 – 13), a computer program product, comprising a computer-readable medium (see column 6, lines 11 – 13) having stored thereon computer executable instructions for implementing a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), said computer executable instructions comprising:

integrating charge in at least some pixels of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 – 59);

combining charge from a first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and column 5, lines 1 – 3) and said at least one

Art Unit: 2612

pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

representing charge from at least a portion of the first region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.);

combining charge from a second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67); and

representing charge from at least a portion of the second region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second region data signals

Art Unit: 2612

(As stated in column 5, lines 34 - 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.).

The CCD spectroscopy of West, as stated in column 3 (lines 10 - 18 and 30 - 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- 19. As for Claim 29, West discloses, as stated in columns 4 (lines 47 67) and 5 (lines 1 4), defining the first region of the N linear pixel arrays of the imaging sensor (300) by designating at least one pixel line (4 or 8 lines) as belonging to the first region (401) of the N linear pixel arrays.
- 20. For Claim 33, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 67), column 5 (lines 1 3, 10 27, and 56 62), and column 6 (lines 11 13), a method for reading data from an imaging sensor (300), said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M charge coupled pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

defining a first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 – 59, and

Art Unit: 2612

column 5, lines 1-3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays;

defining a second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays;

defining a dark region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor, said dark region having a plurality of pixel lines (8 rows; see column 4, lines 47 - 57), said plurality of pixel lines are oriented in generally orthogonal direction to the N linear pixel arrays and said plurality of pixel lines are not exposed to light (see column 4, lines 31 - 34);

receiving a first image (multiline spectroscopy mode) on at least some of the pixels of the first region (401) of the N linear pixel arrays (see column 5, lines 10 - 40);

receiving a second image (multiline spectroscopy mode) on at least some of the pixels of the second region (402) of N linear pixel arrays (again see column 5, lines 10-40);

integrating charge in at least some pixels of the first region (401) of the N linear pixel arrays and in the at least some pixels of the second region (402) of the N linear pixel arrays (in at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 - 59);

reading out charge from said dark region (405a – 405d), said charge from said dark region having been shifted from each region (401 and 402) defined on the N linear pixel arrays of the imaging sensor (300; see column 5, lines 10 – 40).

Art Unit: 2612

The CCD spectroscopy of West, as stated in column 3 (lines 10 - 18 and 30 - 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- 21. As for Claim 34, West discloses combining charge integrated in a region (301) in a region of the N linear pixel arrays of the imaging sensors (300) in the N registers by shifting charge from the dark region (405a 405d) along each of the N linear pixel arrays in the N registers; shifting charge from the N registers along a linear path; and representing charge from at least a portion of the region (301) of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N data signals associated with the region (As stated in column 5, lines 34 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.).
- 22. As for Claim 35, West discloses, as stated in column 5 (lines 10 27 and 63 67) and column 6 (lines 1 6), shifting charge from the dark region (405a 405d) of the N linear pixel arrays of the imaging sensor (300) in the N registers; and discarding the charge shifted from the dark region of the N linear pixel arrays of the imaging sensor.
- As for Claim 36, West discloses, as shown in figure 4, wherein the first region is further defined as a third region (403) and a fourth region (404) of the N linear pixel arrays of the imaging sensor.
- 24. As for Claim 37, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N first region data signals; and presenting said portion of N second region data signals

Art Unit: 2612

(West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).

- As for Claim 38, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N third region data signals; and presenting said portion of N fourth region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.)
- 26. As for Claim 39, West discloses, as stated in column 5 (lines 10 40), wherein a sum (binning) of the pixel lines defined in said first region (401), said second region (402) and said dark region (405a 405d) comprises at least M pixel lines.
- As for Claim 40, West discloses, as stated in column 5 (lines 20 40), wherein said plurality of pixel lines of the dark region (405a 405d) of the N linear pixel arrays is defined as at least M/2 pixel lines (see "binning ratio").
- For Claim 41, West discloses, as shown in figures 4 and 5 and as stated in column 4 (lines 29 67), column 5 (lines 1 3, 10 27, and 56 62), and column 6 (lines 11 13), a method for enhancing dynamic range of data read from an imaging sensor [see below for Examiner's interpretation of this portion of the preamble], said imaging sensor (CCD 300) comprising N linear pixel arrays (column 4, lines 3 and 4, indicates a 1340 M rows x 400 N columns CCD 300), each of the N linear arrays (400 N Columns) having M charge coupled

Art Unit: 2612

pixels (1340 M Rows), each pixel charge coupled, and further being coupled to one of N registers (Horizontal Charge Transfer Register 304), the method comprising:

integrating charge in at least some pixels of a first region (401) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 - 59) and at least some pixels of a second region (402) of the N linear pixel arrays, said first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays; and said second region (at least region 402 containing 8 rows are binned in binning row 406, see figure 4) of the N linear pixel arrays of the imaging sensor, said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays;

combining charge from a first region (at least region 401 containing 8 rows are binned in binning row 406, see figure 4) of the N linear pixel arrays of the imaging sensor in the N registers by shifting charge from the first region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 - 59, and column 5, lines 1 - 3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays;

Art Unit: 2612

shifting charge from the at least some pixels of the first (401) and second regions (402) of the N linear pixel arrays along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67) into a dark region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor, said dark region having a plurality of pixel lines (8 rows; see column 4, lines 47 – 57), said plurality of pixel lines are oriented in generally orthogonal direction to the N linear pixel arrays and said plurality of pixel lines are not exposed to light (see column 4, lines 31 – 34);

representing charge from at least a portion of the first region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N first region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.);

combining charge from a second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the second region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67);

Art Unit: 2612

representing charge from at least a portion of the second region of the N linear pixel arrays, shifted out of the N registers, as a corresponding portion of N second region data signals (As stated in column 5, lines 34 – 40, West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302.);

and clearing charge from the dark region of the N linear pixel arrays of the imaging sensor (column 6, lines 1-6).

The CCD spectroscopy of West, as stated in column 3 (lines 10 - 18 and 30 - 43), provides kinetic spectroscopy wherein a single spectrum occupies multiple rows of elements that are binned to increase sensitivity and also provides multiline spectroscopy wherein plural spectra are captured in a large region and binned into a smaller region.

- As for Claim 42, West discloses, as stated in column 5 (lines 34 40), presenting said portion of N first region data signals; and presenting said portion of N second region data signals (West states kinetic spectroscopy may be accomplished by capturing a single spectrum comprising multiple rows in region 302, binning such multiple row spectrum into one or more rows in region 301, and then capturing a subsequent spectrum in region 302. Spectroscopy includes displaying/presenting the captured spectra.).
- 30. As for Claim 43, West discloses wherein said first portion comprises N first region data signals (4 or 8 rows) and said second portion comprises N second region data signals (also 4 or 8 rows).

Page 19

Application/Control Number: 10/612,125

Art Unit: 2612

West states, since both the light and dark alternating area are eight rows high, the resulting arrangement is two rows of a spectrum comprising four binned rows of spectra and tow rows comprising dark charge.

- 32. As for Claim 44, West discloses integrating charge in at least some pixels of a first region (401) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 59) and at least some pixels of a second region (402) of the N linear pixel arrays, said first region (at least region 401 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said first region (401) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 59, and column 5, lines 1 3) and said at least one pixel line of the first region is oriented in generally orthogonal direction to the N linear pixel arrays; and said second region (at least region 402 containing 8 rows are binned in binning row 406; see figure 4) of the N linear pixel arrays of the imaging sensor, said second region (403) having at least one pixel line, and said at least one pixel line of the second region is oriented in generally orthogonal direction to the N linear pixel arrays.
- As for Claim 45, West discloses, as stated in column 6 (lines 1-6), wherein clearing charge from the dark region of the N linear pixel arrays further comprises: shifting charge from the dark region of the N linear pixel arrays of the imaging sensor in the N registers; and discarding the charge shifted from the dark region of the N linear pixel arrays of the imaging sensor.
- As for Claim 46, West discloses, as stated in column 5 (lines 10 40), wherein a sum (binning) of the pixel lines defined in said first region (401), said second region (402) and said dark region (405a 405d) comprises at least M pixel lines.

Art Unit: 2612

As for Claim 47, West discloses, as stated in column 5 (lines 20 – 40), wherein said plurality of pixel lines of the dark region (405a – 405d) of the N linear pixel arrays is defined as at least M/2 pixel lines (see "binning ratio").

- As for Claim 48, West discloses multiline spectroscopy including a plurality of spectra. Furthermore, West discloses, in column 5 (lines 14 9) and column 5 (line 56) column 6 (line 6), wherein said first region (401) of the N linear pixel arrays having a first image (first spectra) projected thereon, and said second region (402) of the N linear pixel arrays having a second image (second spectra) projected thereon.
- As for Claim 49, West discloses multiline spectroscopy including a plurality of spectra. Furthermore, West discloses, in column 5 (lines 14 9) and column 5 (line 56) column 6 (line 6), wherein said first region (401) of the N linear pixel arrays being exposed to a first light source (first spectra), and said second region (402) of the N linear pixel arrays being exposed to a second light source (second spectra)
- As for Claim 50, West discloses integrating charge in at least some pixels of a one other region (403 404) of the N linear pixel arrays (In at least sections 401, 402, 403, and 404; see figure 4 and column 4, lines 47 59), said other region (403 404) of the N linear pixel arrays having at least one pixel line (8 rows; see column 4, lines 49 59, and column 5, lines 1 3) and said at least one pixel line of the other region is oriented in generally orthogonal direction to the N linear pixel arrays;

shifting charge from the at least some pixels of the other region (403 – 404) of the N linear pixel arrays along a linear path (Again, West teaches that the binned spectra rows are reads

Art Unit: 2612

out through horizontal register 304; see column 4, lines 66 and 67) into a dark region (at least region 405a containing 8 rows) of the N linear pixel arrays of the imaging sensor,

for each of the at least other region (403 or 404), combining charge in one of the at least one other region (at least region 402 containing 8 rows are binned in binning row 406, see figure 4) of the N linear pixel arrays in the N registers by shifting charge from said at least one pixel line of the dark region along each of the N linear pixel arrays to each of the N registers (The binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67), and

shifting charge from the N registers along a linear path (Again, West teaches that the binned spectra rows are reads out through horizontal register 304; see column 4, lines 66 and 67).

### Allowable Subject Matter

- Claims 5 13, 17 22, and 30 32 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.
- 40. The following is a statement of reasons for the indication of allowable subject matter:

As for Claims 5 - 13 and 30 - 32, while the closest prior art discloses multiline spectroscopy or kinetic spectroscopy utilizing a CCD image sensor and pixel line binning for binning a plurality of pixel lines from a plurality of different regions on the CCD image sensor to increase spectrum/spectra sensitivity;

The closest prior art does not teach or fairly suggest determining/adjusting an amount of pixel lines belonging to at least one of said plurality of different regions, wherein the amount the

. 2612

Art Unit: 2612

pixel lines relates to the level of improvement in dynamic range or relates to the comparison of a target signal level.

As for Claims 17 - 22, while the closest prior art discloses two modes for spectroscopy including kinetic and multiline, programming the spectroscopy device with the appropriate readout mode, which alters an amount of pixel lines in a region prior to instructing said readout mode, wherein the readout mode alters the readout binning mode such that a four to one binning ratio can be used to compress a large number of rows in into a smaller number of rows, wherein the large number rows may be divided into separate regions of rows having corresponding large and small amplitude signals;

The closest prior art does not teach or fairly suggest re-scaling one of said small-amplitude signals from said first region and said large-amplitude signals from said second region or determining a relationship between said small-amplitude signals of said first channel from said first region, and said large-amplitude signals of said second channel from said second region.

### Cited Prior Art

The prior art made of record and not relied upon is considered pertinent to Applicant's disclosure at least for the reasons that taken alone or in combination provide various apparatuses and corresponding methods of operating thereof for spectroscopy and/or pixel line binning both utilizing an imaging sensor.

Application/Control Number: 10/612,125 Page 23

Art Unit: 2612

### Conclusion

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Justin P Misleh whose telephone number is 571.272.7313. The Examiner can normally be reached on Monday through Friday from 8:00 AM to 5:00 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Ngoc Yen Vu can be reached on 571.272.7320. The fax phone number for the organization where this application or proceeding is assigned is 571.273.3000.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <a href="http://pair-direct.uspto.gov">http://pair-direct.uspto.gov</a>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JPM October 3, 2005

> NGOOYENYU PRIMARY EXAMINEB

					10/30/00A (10-01)
				C	Complete if Known
	*			Application Number	NEW
INFO	DMATION D	ieci (	SCHE	Filing Date	
	INFORMATION DISCLOSURE STATEMENT BY APPLICANT			First Named Investor	Andrew Weeks Kueny
(use as many sheets as necessary)				Art Unit	Unassigned 2612
				Examiner Name	Unassigned
Sheet	1	of	1	Attorney Docket Number	946959-600013

		U.S	S. PATENT DOCU	JMENTS	
		Document Number			
Examiner Initials*	Cite No.	Number - Kind Code (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
	Α	US-5,675,411	Oct. 7, 1997	Brooks et al.	
17	В	US-6,175,383 B1	Jan. 16, 2001	Yadid-Pecht et al.	
1					
		·			
		·			
				•	
					·
	<u> </u>				

	FOREIGN PATENT DOCUMENTS							
		Foreign Patent Document		·				
Examiner Initials*	Cite No.¹	Country Code <sup>3</sup> – Number <sup>4</sup> – Kind Code <sup>5</sup> (il known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T⁵		

	/ / / /				
Examiner Signature	Lyli	16	Date Considered	9/20/05	
Signature	// •				

\*EXAMINER: Initial if preference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

Applicant's unique citation designation number (optional).
 Applicant is to place a check mark here if English language Translation is attached.

•				_	PTO/SB/08B (10-01)	
Substitute for f	form 1449B/P1	ro ·		C mplete if Known		
				Application Number	NEW	
INICODMA'	TION DISC	ופוופת וי	=	Filing Date		
	INFORMATION DISCLOSURE STATEMENT BY APPLICANT (use as many sheets as necessary)			First Named Investor	Andrew Weeks Kueny	
•				Art Unit Unessigned 2612		
				Examiner Name	Unassigned	
Sheet	1	of	1	Attorney Docket Number	946959-600013	

		OTHER PRIOR ART - NON PATENT LITERATURE DOCUMENTS	
Examiner Initials*	Cite No.1	Include name of author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published	T²
4		Technical Manual, "An Introduction to Scientific Imaging Charge-Coupled Devices," Scientific Imaging Technologies, Inc., Beaverton, OR, 1994.	
	:		
·			
·		11	
Examine Signature		Club Date Considered 9/20/25	

\*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

Applicant's unique citation designation number (optional).
 Applicant is to place a check mark here if English language Translation is attached.

# Notice of References Cited Application/Control No. 10/612,125 Examiner Justin P. Misleh Applicant(s)/Patent Under Reexamination KUENY, ANDREW WEEKS Page 1 of 1

# U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
	Α	US-5,986,267 A	11-1999	West, John	250/370.08
	В	US-5,585,847 A	12-1996	Sayag, Michel	348/266
	С	US-6,252,627 B1	06-2001	Frame et al.	348/311
	D	US-5,198,816 A	03-1993	Kalinowski et al.	341/137
	Е	US-6,801,309 B1	10-2004	Nelson, Steve	356/307
	F	US-5,965,910 A	10-1999	Wood, Mark B.	257/231
	G	US-			
	Н	US-		1	
	ı	US-			
	J	US-			
	к	US-			
	L	US-			
	М	US-			

### FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	0					
	Р					
	Q					<u> </u>
	R	,				S
	s					
	Т					<u> </u>
	<u> </u>		1	NON-PATENT DOCUMEN	TS	<u> </u>

	Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)	
		8
U		m
		0
V		유
		<del>~</del>
w		
<del> </del>		
x		
x		

\*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)

Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.